



In re Patent Application of:
WEN ET AL.
Serial No. 10/723,840
Filing Date: NOVEMBER 26, 2003

In the Claims:

1. (Currently amended) A multiple-band antenna having first and second operating frequency bands, comprising:

a first patch structure ~~associated primarily with the first operating frequency band;~~

a second patch structure electrically coupled to the first patch structure ~~and associated primarily with the second operating frequency band;~~

a first slot structure disposed between a first portion of the first patch structure and the second patch structure and associated primarily with the first operating frequency band and having a distal end portion and a proximal end portion; and

a second slot structure disposed between a second portion of the first patch structure and the second patch structure ~~and associated primarily with the second operating frequency band.~~ having a distal end portion and a proximal end portion;

the proximal end portions of the first and second slot structures being substantially parallel to one another, and the distal end portions of the first and second slot structures diverging from one another.

2. (Original) The multiple-band antenna of claim 1, wherein dimensions of the first patch structure and the first slot structure primarily determine the first operating frequency band, gain of the multiple-band antenna in the first operating

In re Patent Application of:
WEN ET AL.
Serial No. 10/723,840
Filing Date: **NOVEMBER 26, 2003**

frequency band, and impedance of the multiple-band antenna in the first operating frequency band.

3. (Original) The multiple-band antenna of claim 2, wherein dimensions of the second patch structure and the second slot structure primarily determine the second operating frequency band, gain of the multiple-band antenna in the second operating frequency band, and impedance of the multiple-band antenna in the second operating frequency band.

4. (Canceled).

5. (Original) The multiple-band antenna of claim 1, wherein the first patch structure is a substantially C-shaped structure comprising a first end portion, a second end portion, and an adjoining portion coupling the first end portion and the second end portion, wherein the second patch structure is electrically coupled to the adjoining portion, wherein the first slot structure is disposed between the first end portion and the second patch structure, and wherein the second slot structure is disposed between the second end portion and the second patch structure.

6. (Original) The multiple-band antenna of claim 5, further comprising:

a feeding point electrically coupled to the second end portion and positioned to overlap the second end portion; and

In re Patent Application of:
WEN ET AL.
Serial No. 10/723,840
Filing Date: **NOVEMBER 26, 2003**

a ground point electrically coupled to the second patch structure and positioned to overlap the second patch structure, wherein the feeding point and the ground point comprise a single feeding port of the multiple-band antenna.

7. (Original) The multiple-band antenna of claim 6, wherein the first patch structure further comprises a bent portion electrically coupling the feeding point to the second end portion, and the second patch structure comprises a bent portion electrically coupling the ground point to the second patch structure.

8. (Original) The multiple-band antenna of claim 7, wherein the bent portion of the first patch structure and the bent portion of the second patch structure respectively position the feeding point and the ground point at a predetermined distance from the first patch structure and the second patch structure.

9. (Original) The multiple-band antenna of claim 1, wherein the first operating frequency band is a Global System for Mobile communications (GSM) frequency band, and the second operating frequency band is a Personal Communication System (PCS) frequency band.

In re Patent Application of:
WEN ET AL.
Serial No. 10/723,840
Filing Date: NOVEMBER 26, 2003

10. (Original) The multiple-band antenna of claim 9, wherein the GSM frequency band is GSM-900, comprising a transmit sub-band of 880-915 MHz and a receive sub-band of 925-960 MHz.

11. (Original) The multiple-band antenna of claim 10, wherein the PCS frequency band comprises a transmit sub-band of 1850-1910 MHz and a receive sub-band of 1930-1990 MHz.

Claims 12 and 13 (Canceled).

14. (Original) The multiple-band antenna of claim 1, wherein the first patch structure and the second patch structure comprise electrically conductive material selected from the group consisting of: copper, aluminum, silver, and gold.

15. (Original) The multiple-band antenna of claim 1, implemented in a wireless mobile communication device selected from the group consisting of: data communication devices, voice communication devices, dual-mode devices enabled for both data and voice communications, cellular telephones, wireless email communication devices, mobile telephones having data communications functionality, personal digital assistants (PDAs) enabled for wireless communications, wireless email communication devices, and wireless modems.

16. (Original) A multiple-band antenna system comprising:

In re Patent Application of:
WEN ET AL.
Serial No. 10/723,840
Filing Date: **NOVEMBER 26, 2003**

a multiple-band antenna having first and second operating frequency bands, comprising:

a first patch structure;

a second patch structure electrically coupled to the first patch structure;

a first slot structure disposed between a first portion of the first patch structure and the second patch structure;

a second slot structure disposed between a second portion of the first patch structure and the second patch structure;

a feeding point electrically coupled to the first patch structure; and

a ground point electrically coupled to the second patch structure,

wherein the first patch structure and the first slot structure form major radiating and receiving structures for the first operating frequency band, and the second patch structure and the second slot structure form major radiating and receiving structures for the second operating frequency band; and a mounting structure comprising:

a first surface; and

a second surface opposite to and overlapping the first surface,

wherein the first and second patch structures are mounted to the first surface, and wherein the feeding

In re Patent Application of:
WEN ET AL.
Serial No. 10/723,840
Filing Date: **NOVEMBER 26, 2003**

point and ground point are mounted to the second surface.

17. (Original) The multiple-band antenna system of claim 16, wherein the multiple-band antenna further comprises mounting bores in the first patch structure, the second patch structure, the feeding point, and the ground point for receiving fasteners to mount the multiple-band antenna to the mounting structure.

18. (Original) The multiple-band antenna system of claim 17, wherein the mounting bores comprise offset mounting bores in the first patch structure offset from a surface of the first patch structure.

19. (Original) The multiple-band antenna system of claim 17, wherein the fasteners comprise mounting pins disposed on the first surface and the second surface of the mounting structure and positioned to be received by the mounting bores.

20. (Original) The multiple-band antenna system of claim 19, wherein the mounting pins comprise heat stakes that are melted to retain the multiple-band antenna on the mounting structure.

In re Patent Application of:
WEN ET AL.
Serial No. 10/723,840
Filing Date: **NOVEMBER 26, 2003**

21. (Original) The multiple-band antenna system of claim 16, installed at a top rear portion of a wireless mobile communication device.

22. (Currently amended) A wireless mobile communication device comprising:

a first transceiver adapted to transmit and receive communication signals in a first frequency band;

a second transceiver adapted to transmit and receive communication signals in a second frequency band; and

a multiple-band antenna connected to the first transceiver and the second transceiver and comprising:

a first patch structure ~~associated primarily with the first frequency band~~;

a second patch structure electrically coupled to the first patch structure ~~and associated primarily with the second frequency band~~;

a first slot structure disposed between a first portion of the first patch structure and the second patch structure ~~and associated primarily with the first frequency band~~ having a distal end portion and a proximal end portion; and

a second slot structure disposed between a second portion of the first patch structure and the second patch structure ~~and associated primarily with the second frequency band~~ having a distal end portion and a proximal end portion;

In re Patent Application of:
WEN ET AL.
Serial No. 10/723,840
Filing Date: **NOVEMBER 26, 2003**

the proximal end portions of the first and second slot structures being substantially parallel to one another, and the distal end portions of the first and second slot structures diverging from one another

23. (Original) The wireless mobile communication device of claim 22, further comprising:

a housing substantially enclosing the wireless mobile communication device and having front, rear, top, bottom, and side surfaces,

wherein the multiple-band antenna is mounted in the wireless mobile communication device adjacent the top and rear surfaces.

24. (Original) The wireless mobile communication device of claim 23, further comprising a keyboard, a display, a speaker, and a microphone mounted within the front surface.

25. (Original) The wireless mobile communication device of claim 22, wherein the first frequency band is a Global System for Mobile communications (GSM) frequency band, and the second frequency band is a Personal Communication System (PCS) frequency band.

26. (Original) The wireless mobile communication device of claim 22, further comprising:

a fine tuning tab connected to the second

In re Patent Application of:
WEN ET AL.
Serial No. 10/723,840
Filing Date: **NOVEMBER 26, 2003**

portion of the first patch structure for tuning the second frequency band;

a pair of fine tuning tabs connected to the first portion of the first patch structure for tuning the first frequency band; and

a tuning slot disposed between the pair of fine tuning tabs in the first portion of the first patch structure for tuning the second frequency band.

27. (Original) The wireless mobile communication device of claim 22, selected from the group consisting of: data communication devices, voice communication devices, dual-mode devices enabled for both data and voice communications, cellular telephones, wireless email communication devices, mobile telephones having data communications functionality, personal digital assistants (PDAs) enabled for wireless communications, wireless email communication devices, and wireless modems.

28. (New) A multiple-band antenna having first and second operating frequency bands comprising:

a first patch structure associated primarily with the first operating frequency band;

a second patch structure electrically coupled to the first patch structure and associated primarily with the second operating frequency band;

a first slot structure disposed between a first portion of the first patch structure and the second patch structure and

In re Patent Application of:
WEN ET AL.
Serial No. 10/723,840
Filing Date: **NOVEMBER 26, 2003**

associated primarily with the first operating frequency band;
a second slot structure disposed between a second
portion of the first patch structure and the second patch
structure and associated primarily with the second operating
frequency band; and

a feeding port comprising

a feeding point electrically coupled to the first
patch structure and positioned to overlap the first
patch structure; and

a ground point electrically coupled to the second
patch structure and positioned to overlap the second
patch structure.

29. (New) A multiple-band antenna having first and
second operating frequency bands comprising:

a first patch structure associated primarily with the
first operating frequency band;

a second patch structure electrically coupled to the
first patch structure and associated primarily with the second
operating frequency band;

a first slot structure disposed between a first portion
of the first patch structure and the second patch structure and
associated primarily with the first operating frequency band;

a second slot structure disposed between a second
portion of the first patch structure and the second patch
structure and associated primarily with the second operating
frequency band;

In re Patent Application of:

WEN ET AL.

Serial No. 10/723,840

Filing Date: **NOVEMBER 26, 2003**

a first tuning structure connected to the second portion of the first patch structure and comprising a fine tuning tab for tuning the second operating frequency band;

a second tuning structure connected to the first portion of the first patch structure and comprising fine tuning tabs for tuning the first operating frequency band; and

a third tuning structure disposed in the first portion of the first patch structure, comprising a tuning slot for tuning the second operating frequency band.